

- INDUSTRIAL LUBRICANTS
- SYNTHETIC LUBRICANTS
- METALWORKING FLUIDS
- INDUSTRIAL CLEANERS
- SPECIALTY PRODUCTS
- HAZ & NON-HAZ DISPOSAL
- HAZ & NON-HAZ RECOVERY
- HAZ & NON-HAZ RECYCLING
- OTHER ENVIRONMENTAL SERVICES



US Industrial Fluids, LLC

460 Downes Terrace
Louisville, KY 40214

Phone: 502-363-5600
Fax: 502-363-2244
Email: diane@usif.biz

US GEAR EP 220



US Industrial Fluids, LLC

QUALITY BLENDED IN EVERY GALLON

US Gear EP 220 is an high performance gear oil having excellent extreme pressure characteristics and superior load-carrying properties, This lubricant can be used in all types of enclosed gear drives with circulation or splash lubrication systems. It is formulated from highly refined virgin base stocks and a state of the art additive system that provides an extremely high level of resistance to oxidation and chemical degradation. It has friction-modifying characteristics that reduce power consumption and maintain lower bulk oil temperatures. US Gear EP 220 protects against corrosion and rusting. It has outstanding water separating properties and is strongly resistant to foaming in service.

Typical Physical Properties

TEST	METHOD	220
Specific Gravity	ASTM D-287	.89
Flash Point F	ASTM D-92	505
Pour Point F	ASTM D-97	+13
Viscosity SUS @ 100F	ASTM D-445	1162.7
SUS @ 210F		97.2
cSt @ 40C		220
cSt @ 100C		19.1
Rust Test	ASTM D-665A	Pass
Viscosity Index	ASTM D-2270	98
Copper Strip Corrosion	ASTM -130	1B