

UNICUT 16 NFW

- INDUSTRIAL LUBRICANTS
- SYNTHETIC LUBRICANTS
- METALWORKING FLUIDS
- INDUSTRIAL CLEANERS
- SPECIALTY PRODUCTS
- HAZ & NON-HAZ DISPOSAL
- HAZ & NON-HAZ RECOVERY
- HAZ & NON-HAZ RECYCLING
- OTHER ENVIRONMENTAL SERVICES



US Industrial Fluids, LLC

460 Downes Terrace
Louisville, KY 40214

Phone: 502-363-5600
Fax: 502-363-2244
Email: diane@usif.biz



US Industrial Fluids, LLC

QUALITY BLENDED IN EVERY GALLON

Unicut 16 NFW is a high-performance multi-purpose cutting oil. It is free of active sulfur and is non-staining. Unicut 16 NFW is free from chlorine and is non-corrosive. Designed for light to moderate duty cutting operations, it is formulated with very high quality base oils and state-of-the-art additives. This additive technology provides effective machining performance in a wide variety of operations of both ferrous and non-ferrous environments. Unicut 16 NFW is light-colored and transparent so that the work area can be clearly seen at all times.

Recommended for

machining:

Aluminum

Magnesium

Copper

Brasses

Bronzes

Cast irons

Steels (Up to Brinell
hardness of 200)

Other Operations:

It can be used for severe cutting operations of difficult-machine non-ferrous alloys such as silicon-copper, silicon-bronze and copper-nickel. .

Physical Characteristics

TEST	SPECIFICATION
Specific Gravity	0.86
Flash Point F	>400F
Viscosity SUS @ 100 F	4.0
Viscosity cSt @ 40 C	17.0
Odor	Mild Petroleum
Appearance	Yellow Liquid